

Type 2 & 3 SPD with 100A Double Pole Main Switch & 32A MCB
 Complete in a Metal Enclosure
 For TNC-S, TN-S and TT Installations



- Type 2/3 single phase surge devices ideal for domestic installations
- Fully compliant to BSEN61642-11, BSEN62305 & BS7671
- Visual status indication
- This device is **earth leakage free** so may be connected before or after your RCD or RCBOs for easy installation
- Metal Enclosure Designed to BS EN 61439
- 100A Double Pole Main Switch
- 32A OCPD as per BS7671:2018
- Please note that for installations with an overhead supply, this device is unsuitable. You will require a type 1 device.

Part No. SY2DMSENCMETM

SPD According to		IEC61643-1 EN61643-11 Type 2/3
Rated voltage (Max. continuous operating voltage)	U _c	275 V
Nominal discharge current (8/20µs)	I _n	L-N 10kA N-PE 20kA
Max. discharge current (8/20µs)	I _{max}	L-N 20kA N-PE 40kA
Voltage protection level	U _p	< 1.5kV
Response time	t _A	< 25ns
Max. backup device		32A
Terminal capacity		1.5-6mm ²
Dimensions		W 18mm H 90mm D 66mm
Visual Indication of Status		Black OK Red Replace Module
DIN rail mountable		Yes



Part No. SY2D



Tel: 01484 851747

www.surgedevices.co.uk